

Model	SE 200	SE 250	SE 325
	750 / 1000	1000 / 1500	1000 / 1500 / 2000 / 3000
Swing over bed	16"	20"	26"
Swing over carriage	13.25"	17"	23"
Swing over cross slide	9.25"	12"	17.25"
Center distance	30" / 40"	40" / 60"	40" / 60" / 80" / 120"
Spindle speed ranges	3	3	3
Spindle speeds (rpm)	0 - 2800	0 - 2300	0 - 1700
Spindle power (hp)	5.4	7.4	10
Spindle bore	1.5"	2.25"	3"
Spindle nose	A2-5 Camlock	A2-6 Camlock	A2-8 Camlock
Spindle taper	MT 4	MT 4	MT 5
Cross slide travel	7.25"	9.25"	11.75"
CNC Control	Siemens 808D	Siemens 808D	Siemens 808D
Standard Accessories: Siemens 808D CNC control, Electronic hand wheel for X and Z axes, Variable speed headstock with 3 speed ranges, Automatic lubrication for slide ways, Full enclosure, Chip tray, Coolant system, Tailstock, Full enclosure, Work light, Manual quick change 5 position tool post, CE compliant.			
Optional Accessories: Fagor 8037T or Fagor 8055i CNC control, Automatic 8 station turrets, Larger spindle bores, 3-jaw and 4-jaw chucks, Face plates, Steady rests, Follow rests, Tool posts and tool holders, Chip conveyor, and more.			