

Model	SC 200	SC 250	SC 325
	750 / 1000	1000 / 1500	1000 / 1500 / 2000 / 3000
Swing over bed	16"	20"	26"
Swing over carriage	13"	17"	23"
Swing over cross slide	9.5"	12"	18"
Center distance	30" / 40"	40" / 60"	40" / 60" / 80" / 120"
Spindle speed ranges	3	3	3
Spindle speeds (rpm)	40 - 2800	40 - 2300	30 - 1700
Spindle power (hp)	5.4	7.4	10
Spindle bore	1.5"	2.5"	3"
Spindle nose	A2-5 Camlock	A2-6 Camlock	A2-8 Camlock
Spindle taper	MT 4	MT 4	MT 5
Cross slide travel	8"	9.75"	12.75"
Tool post slide travel	4"	5"	6"
Standard Accessories: Centralized lubrication, Tailstock, Chip tray, Coolant system, Threading (Metric, Whitworth, Modular, Diametral), Chuck guard, Rear splash guard, Work light, Tool post, Spindle brake, CE compliant.			
Optional Accessories: Larger spindle bores, 3-jaw and 4-jaw chucks, Face plates, Steady rests, Follow rests, Tool posts and tool holders, Digital Read Outs, and more.			